



F-104^o Solvent Degreaser



FEATURES

- Heavy-duty degreaser removes grease and oil
- Safe to use on all metals and most surfaces
- Controlled evaporation
- No rinsing and low residue
- Alternative to MEK and chlorinated solvents
- 104°F (40°C) flash point
- Inverta Spray Valve allows one to spray in an upright or inverted position

APPLICATIONS

- Aircraft Structures
- Chains
- Gears
- Cables
- Cranes
- Cowlings
- Forklifts
- Air Compressor
- Bonding Prep
- Power Tools
- Landing Gear
- Terminals

PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Color	Clear, off-white
Odor	Orange
Melting / Freezing Point	Not established
Boiling Point / Range	>302°F (>150°C)
Flash Point	104.0°F (40.0°C) Tag Closed Cup (dispensed liquid)
Evaporation Rate	>0.1 BuAc
Flammability	Lower(%): 0.7%; Upper(%): 6%
Vapor Pressure	<5 mm Hg @ 20°C
Vapor Density	>1
Water Solubility	< 15%
Auto-Ignition Temperature	>392°F (>200°C)
Viscosity	< 3 cSt @ 25°C
Percent volatile	100%
VOC Content	Aerosol: 97.2%, Bulk: 100% per US State and Federal Consumer Product Regulations
Specific Gravity	0.82 - 0.86 @ 20°C
Propellant	Aerosol: Petroleum Gases, Liquefied; Bulk: N/A

DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

HANDLING

Aerosol - Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. (See Section 7 of the SDS.)

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. (See Section 7 of the SDS.)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

US	Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
	Canada	Europe				
04920	C04920	M04920	15 wt oz / 425 g / 532 mL	aerosol	12	15 lbs
04955	C04955		55 gal / 208 L	drum	1	400 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved