



Molub-Alloy Paste White T

White paste for clean assembly work, prevents fretting corrosion

Description

MOLUB-ALLOY™ PASTE WHITE T (previously named Optimol™ Paste White T) is excellently suited for all assembly work as well as for base or thin-film lubrication. White, almost colorless when applied as thin layer. The paste prevents fretting corrosion and facilitates assembly and disassembly. It is resistant to hot and cold water and protects against corrosion.

Application

- Universal application as assembly paste.
- Prevents fretting corrosion especially when exposed to vibrations Avoids stick-slip.
- For machines subject to frictional vibrations.
- Avoids squeaking noises in hydraulic cylinders and open lubrication points Temperature application range: - 30°C/-22°F to +250°C/+482°F

Advantages

- Clean application.
- Easy assembly and disassembly .
- Prevents fretting corrosion.
- Good separating property for all types of contact.
- Resistant to hot and cold water.
- Good corrosion protection.

Typical Characteristics

Name	Method	Units	
Colour	Visual	-	white
Base	-	-	Mineral oil
Worked Penetration (60 strokes @ 25°C / 77°F)	ASTM D217 / ISO 2137	0.1 mm	310-340
Density @ 20°C / 68°F	Inhouse method	kg/m ³	1160
Water Resistance	DIN 51807-1	Rating	1
Rust Test - EMCOR (distilled water)	ASTM D6138 / ISO 11007	Rating	0
Erichsen Screw test	DIN EN ISO 16047	total friction	0.11

Subject to usual manufacturing tolerances

Additional Information

- Clean surface. Apply even layer of MOLUB-ALLOY PASTE WHITE T with a brush or a lint-free cloth.
- For paste-specific applications - cannot replace oil or grease lubrication.
- Shake spray can well before use; spray thin and even layer onto lubricating surface.
- In spray cans: MOLUB-ALLOY PASTE WHITE T SPRAY.

This product was previously named Optimol™ Paste White T. The name was changed in 2015.

Molub-Alloy Paste White T

23 Oct 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 352, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0345 9645111 Technical Enquiries: 0345 082 1719
www.castrol.com/industrial