



Instant Super Degreaser



FEATURES

- Heavy-duty action removes oil, grease, wax, dirt, moisture, tar, and other contaminants
- Heavy-duty performance
- Power blast spray
- Removes oil, grease, dirt and tar
- Non-flammable, and non-conductive
- Does not contain chlorinated solvents
- Fast evaporating
- No rinsing, no residue
- Safe on most metals

APPLICATIONS

- Air Compressors
- Bearings
- Cables
- Chains
- Forklifts
- Gears
- Heavy Equipment
- Power Tools

SPECIFICATIONS AND APPROVALS

- Airbus ABR 9-0140 Issue 5A Type I
- Boeing D6-17487 Rev. P
- Canadian Food Inspection Agency
- Kimberly-Clark
- McDonnell Douglas CSD #1
- NSF International, C1

PROPERTIES

Appearance / Physical State	Gas/Aerosol
Odor	Strong
Melting / Freezing Point	-166 °F (-110 °C) (estimated based on nPB)
Boiling Point / Range	158°F (70 °C)
Vapor Pressure	134 mm Hg @ 25°C
Partition Coefficient	Not available
Percent volatile	100%
Flammability	Flammability limit - lower (%) 3.8 % Flammability limit - upper (%) 9.5 %
Propellant	Carbon dioxide
VOC Content	96.5% per US State and Federal Consumer Product Regulations
Color	Colorless to light yellow
Flash Point	None. ASTM D-56 TCC (Liquid portion)
Density	Not available
Evaporation Rate	4.7
Vapor density	4.24 (estimated based on nPB)
Auto-Ignition Temperature	> 914°F (>490°C) (estimated based on nPB)
Viscosity	Not available
Specific Gravity	1.34 - 1.36
Temperature Range	Not applicable
4-Ball Weld Load	Not applicable

DIRECTIONS

Spray on parts and equipment. Allow flushing action to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

HANDLING

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. (see Section 7 of the SDS)

STORAGE

Store locked up. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. (see Section 7 of the SDS)

DISPOSAL

Contents under pressure. Do not puncture, incinerate or crush. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Case Weight
US	Canada				
00755 (min qty req)		55 gal	drum	1	
00720	C00720	20 wt oz / 567 g / 441 mL	aerosol	12	19 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved