

Issued 7/22/2013

**Description:**

**BONDERITE L-GP GP 460 ACHESON (known as ACHESON GP-460)** is an anti-seize lubricant containing high purity graphite in petrolatum. This material is designed to provide long-lasting service over a wide temperature range. It withstands extreme pressure, carries high loads, and reduces friction, galling, and seizing. **BONDERITE L-GP GP 460 ACHESON (known as ACHESON GP-460)** meets the requirements of General Electric specification A50TF201.

**Typical Applications:**

- Anti-seize lubrication in refinery, chemical, industrial, and steam-generated plants
- Anti-seize lubrication in salt-laden areas
- Anti-seize lubricant for high temperature service on aircraft engine spark plugs, threaded fasteners and fittings

Examples:	Splines	Bolts	Bushings	Tractor Links
	Couplings	Gears	Seals	Drag Lines
	Flanges	Bending	Press Fits	Valve Stems
	Studs	Plugs	Coining	Cold Extrusion
	Tappings	Bearings	Wire Drawing	Adjusting Screws

**Physical Properties:  
(as supplied)**

Lubricating pigment	: graphite
Carrier	: petrolatum
Consistency	: paste
Solids content	: 50%
Density	: 10.8 lb/gal (1.29 kg/l)
Flash point	: 400°F (200°C) minimum
Operating temperature	: 1000°F (538°C) maximum
Shelf life	: 2 years from date of qualification under original seal.

**Method of Use:**

**BONDERITE L-GP GP 460 ACHESON (known as ACHESON GP-460)** is supplied ready for use. Apply by brush, swab, or hand grease gun. It is not intended to be used in pressurized lubrication systems due to high solids content.

**Companion Products:**

**Henkel** carries a full line of anti-seize lubricant products (BONDERITE L-GP GP 400 ACHESON series products).

---

**Precautions:**

Harmful if swallowed. May cause eye irritation. Wash thoroughly after handling. Keep container tightly closed when not in use to avoid contamination. (See Henkel Material Safety Data Sheet for proper first aid instructions.)

**APPLICATION ASSISTANCE**

Henkel's Application Specialists are available to assist you in production start-up with **BONDERITE L-GP GP 460 ACHESON (known as ACHESON GP-460)**. For more information, contact Henkel, 866.332.7024, or visit our website at [www.henkelna.com/metals](http://www.henkelna.com/metals) for the Henkel global location nearest you.

**HEALTH & SAFETY**

Harmful if swallowed, inhaled, or absorbed through skin. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Keep container tightly closed when not in use. Use with adequate ventilation. Avoid breathing vapor. See Henkel's Material Safety Data Sheet for proper first aid instructions.

---

Henkel Corporation | 32100 Stephenson Highway | Madison Heights, MI 48071  
PHONE: (248) 583-9300 | FAX: (248) 583-2976 | [www.henkelna.com/](http://www.henkelna.com/)

**Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

