

# ANDEROL PRODUCT DATA SHEET

## **ROYCO® C-201**

HIGH TEMPERATURE FLUOROSILICONE

GREASE AND SPLINE LUBRICANT

### **GENERAL INFORMATION**

ROYCO C201, a brown-colored fluorosilicone based grease utilizing a PTFE type thickener for enhanced load carrying capability and an additive package containing antioxidants, corrosion inhibitors, and heat stabilizing additives.

### **TYPICAL PROPERTIES:**

PROPERTIES	TEST METHOD	ROYCO C-201
Penetration, mm	ASTM D-217	
Unworked		280
Worked		295
Dropping Point, °C (°F)	ASTM D-566	>260 (500)
Water Resistance, 37.8°C, % loss	FTM 791B-321.2	Nil
Copper Corrosion, 24 hrs, 100°C		1b
Load Wear Index	ASTM D-130	65
Evaporation, 24 hrs @ 204°C, % loss	ASTM D-2783	2.5
Rust Protection, 100% RH, 14 days	---	No rust or staining
Low Temperature Torque, -51°C, g-cm		
Starting		3,900
Running	ASTM D-972	2,400

**ROYCO C-201**

®ANDEROL is a reg. trademark of ANDEROL Inc.

**For more information please refer to the relevant Material Safety Data Sheet accompanying each product.**

This information is furnished without warranty, representation, inducement, or license of any kind, except that it is accurate to the best of OUR knowledge or obtained from sources believed by ANDEROL to be accurate. ANDEROL does not assume any legal responsibility for use of reliance upon it. Only chemists or chemically qualified lab technicians should carry out tests. Before using any chemical, read its label and Material Safety Data Sheet.

## APPLICATIONS

Intended for high temperature applications requiring good load carrying capability. Typical uses include high temperature spline couplings, bearings, actuators, or other aggressive environments in the temperature range of -50 to +500 degrees F (-45 to +260°C).

## ADVANTAGES

- Wide operating temperature range
- Excellent low temperature properties
- Very low evaporation and volatility characteristics
- Corrosion and rust inhibited

## COMPATABILITY

Description of compatibility issues.

## APPROVALS

ROYCO C-201 has been approved by the Vickers AOM Div. of Sperry Rand Corp. for use as a spline lubricant in the coupling of PV3-115 and PV3-240 hydraulic pumps.

RC-201: 11/30/01: edited 10/22/04 by GMG



ANDEROL Inc.  
PO Box 518, 215 Merry Lane  
East Hanover, New Jersey USA  
Tel: 888-ANDEROL  
Or Tel: (973) 887-7410  
Fax: (973) 884-3825  
E-mail: [info@anderol.com](mailto:info@anderol.com)