

D-5015NS



Product description:

AVIONIC CORROSION PREVENTIVE Mil-PRF-81309H TYPE III, CLASS 2 GRADE B: CO₂)

FEATURES:

- Provides a light, soft, and ultra-thin film with moisture displacing properties
- A light duty version of D-5026NS

KEY BENEFITS:

- Contains lubricating properties to prevent fretting corrosion and erosion of the connector's plated surface
- Protects electrical connectors from corroding
- Excellent for "overnight" tooling protection on highly critical surfaces
- Displaces water from electrical and electronic components



- One aerosol can covers approximately 120 ft² (11.1m²)
- Formulated for use on highly critical metal surfaces and avionic components
- Leaves a thin film with less product build up when compared to D-5026NS
- Thin protective barrier coating of D-5015NS prevents corrosion

Rev: 29070B 11-30-2021







D-5015NS



Product description:

AVIONIC CORROSION PREVENTIVE Mil-PRF-81309H TYPE III, CLASS 2 GRADE B: CO₂)

SPECS:

- Lockheed EMAP G39.032
- Mil-PRF-81309H Type III Class 2 Grade B: CO₂
- Sikorsky SS8536

APPLICATIONS:

- ✓ **D-5015NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit®** technical data sheet for more information.
- ✓ Bulk application available as ZC-015
- ✓ For removal of D-5015NS, use D-5640NS, Sur-Prep® 3160, or Sur-Prep® 3167

PHYSICAL PROPERTIES:

- Evaporation Rate: Faster than ether
- ► Flame Extension: Flammable
- ► Specific Gravity (H₂O=1): 0.9
- Vapor Density: Heavier than air







D-5015NS



Product description:

AVIONIC CORROSION PREVENTIVE Mil-PRF-81309H TYPE III, CLASS 2 GRADE B: CO₂)

AVAILABLE PACK SIZES:

- 16 fl oz (473 ml) Aerosol-007670
- Case of 4 each Gallon (4 each of 3.8 L) Cans-009413
- ► 5 Gallon (18.9L) Pail-002089
- ▶ 55 Gallon (208L) Drum-002090
- Special Packaging Upon Request

