

D-5029NS



Product description:

CORROSION INHIBITING COMPOUND BMS 3-29

FEATURES:

- A long lasting, high solids, low volatiles, high penetration, and water displacing corrosion inhibiting compound
- Non-tacky with a light, amber tint

KEY BENEFITS:

- Fast drying and non-tacky
- Non-cracking and flaking up to -40°F (-40°C)
- Contains a detectable film
- Solvent removable
- > 1500 hours of salt spray
- High Solids > 51%

SPECS:

- BMS 3-29 (Meets or Exceeds)
- DMS 2150 Type 1 & Type 2 (Meets or NSN: 6850-01-355-3387 (Meets or Exceeds) Exceeds)
- NSN: 8030-01-501-6622 (Meets or Exceeds)

Rev: 29089B 01-06-2022







D-5029NS



Product description:

CORROSION INHIBITING COMPOUND BMS 3-29

APPLICATIONS:

- ✓ Use D-5029NS on high profile aircraft substrates
- ✓ Easily apply corrosion inhibiting compound via aerosol
- ✓ **D-5029NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit®** technical data sheet for more information.
- ✓ Apply at 2-3 mils (51-76 microns) of wet thickness.
- ✓ One aerosol can coats approximately 50 ft² (4.7m²)
- ✓ Bulk application available as ZC-029

PHYSICAL PROPERTIES:

Color: Transparent Amber

Drying Time: <12 hours</p>

► Flash Point: 122°F (50°C)

Non-Volatiles: 51% min.

Specific Gravity: 0.89

Viscosity: 140 cps.

► Water Displacement: 0% Rust







D-5029NS



Product description:

CORROSION INHIBITING COMPOUND BMS 3-29

AVAILABLE PACK SIZES:

- Case of 12 of 16 fl oz (473 ml) Aerosols-002050
- Case of 4 each Gallon (4 each of 3.8L) Cans-009422
- ► 5 Gallon (18.9L) Pail-002109
- ▶ 55 Gallon (208L) Drum-002110
- Special Packaging Upon Request

