

D-5035NS



Product description:

HIGH TEMPERATURE CORROSION PREVENTIVE

FEATURES:

- ▶ A heat resistant corrosion preventive
- ▶ Provides a firm and waxy coating

KEY BENEFITS:

- ▶ **D-5035NS** is formulated to provide long term protection against corrosion
- ▶ The **D-5035NS** coating can withstand continuous temperatures up to 350°F (177°C), with a short term exposure up to 430°F (221°C)
- ▶ The **D-5035NS** coating contains excellent moisture displacing qualities and adhesion capabilities

SPECS:

- Boeing QPL for DPM 5217
- NSN: 8030-01-686-7249 (16 fl oz (473 ml) Aerosol)



- ▶ The **D-5035NS** coating provides over 1300 hours of protection on steel in a salt fog environment
- ▶ The **D-5035NS** coating provides superior dampening to metal
- ▶ The **D-5035NS** coating contains acid neutralization properties

Rev: 20067G
11-30-2021

D-5035NS



Product description:

HIGH TEMPERATURE CORROSION PREVENTIVE

APPLICATIONS:

- ✓ A dry film thickness of 1.0 mil (25 microns) provides a transparent coating
- ✓ The **D-5035NS** aerosol can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit®** technical data sheet for more information.
- ✓ Bulk application available as **ZC-035**
- ✓ Firm and waxy coating of **D-5035NS** can be easily removed with petroleum solvents

PHYSICAL PROPERTIES:

- ▶ **Evaporation Rate:** Faster Than Ether
- ▶ **Fungal Growth per Fed-STD-810 Method 508.7:** 0 (No Microbial Growth)
- ▶ **Material V.O.C.:** 583 g/L (4.8 lbs/gal)
- ▶ **Melt Point:** 550°F (28°C)
- ▶ **Specific Gravity:** 0.8
- ▶ **Vapor Density:** Heavier Than Air

AVAILABLE PACK SIZES:

- ▶ Case of 12 of 16 fl oz (473 ml) Aerosols-002052
- ▶ Special Packaging Upon Request