

ZC-029



Product description: CORROSION INHIBITING

COMPOUND

FEATURES:

- A long lasting, high solids, low volatiles, high penetration, and water displacing corrosion inhibiting compound
- Non-tacky with a light amber tint

KEY BENEFITS:

- > 1500 hours salt spray on aluminum (Al)
- ► Fast drying and non-tacky
- Non-cracking and flaking up to -40°F (-40°C)
- Has a detectable film
- Solvent removable
- Very low dry weight film
- ► High Solids > 51%

SPECS:

- BMS 3-29
- DMS 2150 Type 1 & Type 2

• NSN: 8030-01-501-6622

NSN: 6850-01-355-3387

ZC-029
Along lasting, high penetration and water displacing CIC
FOR HIGH PROFILE AIRCRAFT SUBSTRATES

Net Contents: 1 Gallon

Rev: 29087F 11-30-2021





ZC-029



Product description:

CORROSION INHIBITING COMPOUND

APPLICATIONS:

- ✓ Apply via airless or air-operated spray equipment
- ✓ Apply at 2-3 mils (51 to 76 microns) of wet thickness
- ✓ Aerosol application available as D-5029NS
- ✓ Use on high profile aircraft substrates

PHYSICAL PROPERTIES:

Color: Transparent Amber

Drying Time: <12 hours</p>

► Flash Point: 122°F (50°C)

Non-Volatiles: 51% min.

► Specific Gravity: 0.89

▶ Viscosity: 140 cps.

► Water Displacement: 0% Rust







ZC-029



Product description:

CORROSION INHIBITING COMPOUND

AVAILABLE PACK SIZES:

- Case of 12 of 16 fl oz (473 ml) Aerosols-002050
- Case of 4 each Gallon (4 each of 3.8L) Cans-009422
- ► 5 Gallon (18.9L) Pail-002109
- ▶ 55 Gallon (208L) Drum-002110
- Special Packaging Upon Request

