

# Aero-Lube™

LUBRICANTS & LUBRICATING COMPOUNDS

**D-5933NS**



## *Product description:* **AEROSOLIZED GREASE**

### **FEATURES:**

- ▶ Contains Shell Oil Company's Aeroshell® Grease 33, a multipurpose airframe grease
- ▶ Made with a synthetic base oil and a lithium complex thickener

### **KEY BENEFITS:**

- ▶ Provides enhanced corrosion resistance and load-carrying capacity
- ▶ Reduces expense of wasting lubricant
- ▶ **D-5933NS** contains a useful temperature range of -100° F (-73°C) to +250° F (+121°C)
- ▶ Non-flammable
- ▶ Saves valuable time and labor
- ▶ Applies a clean and uncontaminated layer of grease where it is needed
- ▶ Non-toxic



### **SPECS:**

- Boeing QPL for BMS 3-33C Type 2
- MIL-PRF-23827C Ty 1 (Aeroshell® 33 grease)

Rev: 29065E  
10-21-2021

 For more information contact us :  
[zipchem@addevmaterials.com](mailto:zipchem@addevmaterials.com)

 Part of 

**D-5933NS****Product description:**  
**AEROSOLIZED GREASE****APPLICATIONS:**

- ✓ **D-5933NS** should not be used to replace lubrication that was achieved by grease gun application through zerk fittings
- ✓ Can be used in combination with a snorkel
- ✓ In use, the non-toxic, non-flammable propellants vaporize so that the lubricant is the only liquid that is left behind.
- ✓ Use where drawings or maintenance manuals allow the use of hand or brush application of bulk grease
- ✓ **D-5933NS** can be used in conjunction with the **Formit**® extensions to provide targeted spray to areas that may be difficult to reach but need to be coated. Please refer to the **Formit**® technical data sheet for more information.
- ✓ Use as a replacement for molybdenum disulfide in problem areas like the tailing edge flaps
- ✓ Other applications include the general airframe lubricant, highly loaded gears, actuator screw mechanisms, instruments, and all sliding and wiping surfaces with moisture entrapment problems

**PHYSICAL PROPERTIES:**

- ▶ **Color:** Green
- ▶ **Mean Hertz Load, Kg:** 60
- ▶ **Melting Point:** None
- ▶ **Grease Operating Temperature:** -100 to +250°F (-73°C to 121°C)
- ▶ **Spray Application Temperature Range:** 20° F to 120° F (-7°C to 49°C)
- ▶ **Water Resistance, % w Loss@ 175°F (79°C):** <6

The logo for Aero-Lube, featuring the brand name in a bold, sans-serif font with a trademark symbol. The background of the entire page is a photograph of an aircraft engine in a hangar.

LUBRICANTS & LUBRICATING COMPOUNDS

**D-5933NS**



*Product description:*  
**AEROSOLIZED GREASE**

---

**AVAILABLE PACK SIZES:**

▶ 10 fl oz (296 ml) Aerosol-008431

---

Aeroshell® Grease 33 is a Shell Oil Co. registered trademark.

 For more information contact us :  
[zipchem@addevmaterials.com](mailto:zipchem@addevmaterials.com)

 Part of  **ADDEV MATERIALS**