



# ZeroTri® Heavy-Duty Degreaser



## FEATURES

- Fast acting solvent for degreasing parts and equipment
- Penetrating action instantly removes oil, grease, wax, dirt, moisture, and other contaminants
- Heavy-duty penetrating degreaser
- No ozone depleting chemicals
- No rinsing, no residue
- Does not contain chlorinated solvents

## APPLICATIONS

- Air Compressors
- Bearings
- Chains
- Cranes
- Forklifts
- Gears
- Ink Removal from Printing Presses
- Pulleys

## SPECIFICATIONS AND APPROVALS

- Boeing BAC 5750 Rev. J
- NSF International, C1 (Aerosol)
- NSF International, C1 (Bulk)
- Pratt & Whitney Canada MMC 21530
- NSF International, C1(Non-Aerosol)

## PROPERTIES

<b>Appearance / Physical State</b>	Aerosol: Gas, Bulk: Liquid
<b>Color</b>	Colorless. Clear.
<b>Odor</b>	Ether-like. Fruity.
<b>Melting / Freezing Point</b>	Not established
<b>Boiling Point / Range</b>	> 132.8°F (> 56°C)
<b>Flash Point</b>	1.4°F (-17.0 °C) Tag Closed Cup
<b>Evaporation Rate</b>	> 1 (BuAc = 1)
<b>Flammability</b>	Flammability limit - lower (%) 1.2% Flammability limit - upper (%) 12.8%
<b>Vapor Pressure</b>	> 75 mm Hg @ 20°C
<b>Vapor density</b>	~ 3 (air = 1)
<b>Density</b>	Not available.
<b>Water Solubility</b>	35% w/w
<b>Partition Coefficient</b>	Not available.
<b>Auto-Ignition Temperature</b>	Not established
<b>Viscosity</b>	Not established
<b>Percent volatile</b>	100%
<b>Specific Gravity</b>	0.74 - 0.76 @ 20°C
<b>VOC Content</b>	Aerosol: 62.4%, Bulk: 65%
<b>Propellant</b>	Carbon dioxide (Aerosol)

## DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

## HANDLING

"Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. (See Section 7 of the SDS)"

## STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat and sources of ignition. (See Section 7 of the SDS)

## DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

## AVAILABLE PRODUCTS

US	Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
	Canada	Europe				
03520	C03520	M03520	15 wt oz / 425 g / 563 mL	aerosol	12	15 lbs
03528	C03528		1 gal / 3.78 L	can	4	30 lbs
03505	C03505		5 gal / 18.93 L	pail	1	36 lbs
03555	C03555	M03555	55 gal / 208 L	drum	1	346 lbs
		M03515	5 L	pail	1	
		M03505	20 L	pail	1	



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved